



## Power Distribution Unit

Product Code/Part Code:EAM-S320A-BE335VX

### Specification Sheet:

---

#### Input

• Voltage:	1 $\Phi$ , 230VAC
• Frequency:	50 Hz / 60Hz (As per supply input)
• Power In Socket Type:	1 $\Phi$ , 16Amps, IEC 60309(P+N+E), 230VAC
• Cord Length:	3 meter
• Input Current:	16Amps

#### Output

• Voltage:	230VAC
• Frequency:	50Hz / 60Hz (As per supply input)
• Power out Socket Type:	IEC-320 C13 (18 Nos.) & IEC-320 C19 (2 Nos.)
• Current Operating range:	16Amps

#### Features

- Aggregate Current Monitoring: Monitors the aggregate / Total current flowing through the device
- Monitors & Tracks Aggregate Power Consumption
- Conforms to CLASS I measurement accuracy
- Total No. of outlets: 20 - IEC-320 C13 (18 Nos.) & IEC-320 C19 (2 Nos.)
- Monitoring & Metering of electric parameters: Voltage (V), Current (I), Energy (kWH) Power (kVA, kVAR), Power factor (cos  $\Phi$ )
- Current Threshold Settings with warning LED on front panel & Buzzer alarm.
- LED Display of Aggregate Current on front panel.
- Provision to connect Temperature / Humidity Sensor.
- **Branch Circuit Protection : 16A Hydraulic Magnetic Circuit breaker**



## User Interface:

- Integrates with any DCIM System through SNMP

## Interface and Protocol Support

- HTTP
- SNMP
- MODBUS TCP/IP

## Mechanical

- Dimensions (L x W x H): 1350mm x 50mm x 75mm
- Weight: Approx.5.300 Kg
- Mounting: 1043.00mm
- Display / control panel: Three digit 7 segment Display
- Color: RAL 9005
- Finish: Fine texture

## Environmental Requirements

- Operating temperature: 0 – 45°C (Extended up to 65°C)
- Humidity: 0 – 95 % RH non-condensing

## Conformance

- Comply with UL 60950
- CE

