



## Power Distribution Unit

Product Code/Part Code:EIS-T630A-EE335VX

### Specification Sheet:

---

#### Input

• Voltage:	3 $\Phi$ , 440VAC
• Frequency:	50 Hz / 60Hz (As per supply input)
• Power In Socket Type:	3 $\Phi$ , 32 Amps, IEC 60309(3P+N+E), 440VAC
• Cord Length:	3.0 meter
• Input Current:	32 Amps

#### Output

• Voltage:	230 VAC
• Frequency:	50Hz / 60Hz (As per supply input)
• Power out Socket Type:	IEC-320 C13 (24 Nos.) & IEC-320 C19 (6 Nos.)
• Current Operating range:	32 Amps

#### Features

- Individual Current Monitoring: Monitors the Individual / Total current flowing through the device
- Individual Switching: User can control outlet level current , receptacle level control
- Monitors & Tracks Individual Power Consumption
- Conforms to CLASS I measurement accuracy
- Total No. of outlets: 30 - IEC-320 C13 (24 Nos.) & IEC-320 C19 (6 Nos.)
- Socket level Monitoring & Metering of electric parameters: Voltage (V), Current (I), Energy (kWH) Power (kVA, kVAR), Power factor (cos  $\Phi$ )
- LED Display of Aggregate Current on front panel
- Current Threshold Settings with warning LED on front panel & Buzzer alarm
- Provision to connect Temperature / Humidity Sensor.
- **Branch Circuit Protection : Three(3) x 32A Hydraulic Magnetic Circuit breaker**



## User Interface:

- Integrates with any DCIM System through SNMP

## Interface and Protocol Support

- HTTP
- SNMP
- MODBUS TCP/IP

## Mechanical

- Dimensions (L x W x H): 1830mm X 60mm X 85mm
- Weight: Approx 6.0 Kg
- Mounting: 1523.50mm
- Display / control panel: Three digit 7 segment Display
- Color: RAL 9005
- Finish: Fine texture

## Environmental Requirements

- Operating temperature: 0 – 45°C (Extended up to 65°C)
- Humidity: 0 – 95 % RH non-condensing

Product Drawing

