

PRODUCT CODE:- <b>FH-1B SERIES</b>	CATEGORY:- <b>PANEL MOUNTING FUSE HOLDER</b>
---------------------------------------	---

<p><b>BASIC DIMENSIONS:-</b></p>	<p><b>PANEL CUTOUT:-</b></p>
----------------------------------	------------------------------

**SPECIFICATION TABLE:-**

SR NO	PARAMETER	SPECIFICATION	
1	Type	Fuse holder	
2	Panel Thickness	3.0 Max.	
3	Fuse link size	Ø5.0 x 20.0	
4	V/A Rating	6.3A, 250 V AC	
5	CR (Initial)	10 m Ohms Max	
6	IR (500 VDC)	1000 M Ohms Min.	
7	HVT (1Minute)	2 KV AC	
8	Mounting	Panel	
9	Terminals	Solder-type	
10	Permissible Temp For FH-1Series:	(a)with/without load	-20°C TO +85°C
		(b)for soldering	270°C for 5 Sec. Max.
11	Material	(a)Body	Phenolic
		(b)Cap	Nylon
		(c)Terminals	Brass, Tin plating
12	Reference Standard	IEC-60127-6	

**ORDERING CODE:-**

Sr. No	TYPE	CODE	CAP COLOR	
			BLACK	RED
1.	Screw-in Cap with Phenolic body material	FH-1B	FH-1B-03	FH-1B-04

  

APP	28.01.15	GIG	<p>Plot E-4, Kagal Five Star MIDC, Kagal, Kolhapur, MH - 416236, India Elcom International Pvt. Ltd. www.elcom-in.com</p>												
CHK	28.01.15	PGP													
DRN	28.01.15	PPD													
REV	IS	WAS	DATE	SIGN	APP.	BY	DATE	SIGN							
UNSP.TOLERANCE		DIMNS. IN	WT(Gm)	SCALE:-	PROJECTION	SHEET	DRAWING NUMBER								
OVER	- 1 10	mm	Max.	NTS.		1 OF 1	P	F	H	0	2	0	0	1	REVISION
UP TO	± 0.2 0.3 0.5	Moulding, plating details as per Bill of Material Unspecified colour is Black, GF:Glass filled.													
F:ENG-08.00 Note: Technical specifications are subject to change without prior notice Copyright © 2019 by Elcom International Pvt.Ltd, India. All rights reserved															