



Power Distribution Unit

Product Code/Part Code: EIS-S630A-DE335VX

Specification Sheet:

Input

• Voltage:	1 Φ , 230VAC
• Frequency:	50 Hz / 60Hz (As per supply input)
• Power In Socket Type:	1 Φ , 32 Amps, IEC 60309(P+N+E), 230VAC
• Cord Length:	3 meters
• Input Current:	32 Amps

Output

• Voltage:	230VAC
• Frequency:	50Hz / 60Hz (As per supply input)
• Power out Socket Type:	IEC-60320 C13 (24 Nos.), IEC-60320 C19 (06 Nos.)
• Current Operating range:	32 Amps

Features

- Individual Current Monitoring: Monitors the Individual / Total current flowing through the device.
- Individual Switching: User can control outlet level current, receptacle level control.
- Monitors and Tracks Individual power consumption.
- Conforms to CLASS I measurement accuracy.
- Socket level Monitoring and Metering of electric parameters: Voltage (V), Current (I), Energy (kWH) Power (kVA, kVAR), Power factor (cos Φ)
- Current Threshold settings with warning LED on front panel and Buzzer alarm.
- LED Display of Aggregate current on front panel.
- Networking: 10/100 Base Ethernet Port.
- Provision to connect Temperature - Humidity Sensor.
- Hot Swappable Controller.
- Total No. of outlets: 30 - IEC-60320 C13 (24 Nos.), IEC-60320 C19 (06 Nos.)
- Branch Circuit Protection: Two (2) x 16A Hydraulic Magnetic Circuit Breaker



User Interface:

- Integrates with any DCIM System through SNMP.

Interface and Protocol Support

- HTTP
- SNMP V1
- MODBUS TCP/IP
- MODBUS RTU(RS-485)
- FTP
- DHCP
- IPV4 Support
- Telnet

Mechanical

- Dimensions (L x W x H): 1750mm x 60mm x 85mm
- Weight: Approx.6.00 Kg
- Mounting: 1443.50mm
- Display / control panel: Three-digit 7 segment Display
- Color: RAL 9005
- Finish: Fine texture

Environmental Requirements

- Operating temperature: 0 – 45°C (Extended up to 65°C)
- Humidity: 0 – 95 % RH non-condensing

Conformance

Approvals

- cULus

Marking

- CE
- cULus

Environmental Compliance

- RoHS

Product Drawing

